

Discover the Perfect Bio-Fire for Your Home



TermaTech TT20 Streamline R Bio - 69TT20BASRBIO

Weight: 79kg

Dimensions (H/W/D): 956 x 531 x 419 mm

Max Heat Output: 2kW

Capacity: 1L

Consumption: Approx. 3 hours per litre (at lowest level)

Application: For indoor use only. Min 10 °C

TermaTech Biotronic 400 (BEV Technology™) - 69BIO400

Weight: 36kg

Dimensions (H/W/D): 1262 x 400 x 321 mm

Max Heat Output: 3.5kW | Operating Range: 2.8 kW to 3.5 kW

Power supply: 230 V

Capacity: 5L

Consumption: Approx. 5 hours per litre (at lowest level)

Application: For indoor use only. Min 10 °C



TermaTech TT23RG Biotronic (BEV Technology™) - 69TT23RGBIO

Weight: 97kg

Dimensions (H/W/D): 1073 x 521 x 412 mm

Max Heat Output: 3.5kW | Operating Range: 2.8 kW to 3.5 kW

Power supply: 230 V

Capacity: 5L

Consumption: Approx. 5 hours per litre (at lowest level)

Application: For indoor use only. Min 10 °C



Delivery times vary
by model.



Buy online today
www.specflue.com

SOLE DISTRIBUTOR

SPECFLUE



Discover the Perfect Bio-Fire for Your Home



Why Choose a TermaTech Bio-Fireplace?

Real Flame, No Hassle

Experience the warmth and beauty of a real flame—no chimney, flue, or complex installation required. Easy to ignite with adjustable flame control for effortless comfort.

Perfect for Rentals & Flats

No permanent fittings required, making it ideal for apartments, rented homes, and spaces where traditional stoves aren't an option.

Heat Output Similar to an Electric Heater

Efficient and effective, providing a comparable warmth level to an electric heater or radiator while enhancing your home's aesthetic.

Zero Emissions

Powered by bioethanol, a clean-burning fuel that produces no harmful emissions or pollutants—an environmentally friendly choice.

Real flames, real heat - no limits.



Delivery times vary
by model.



Buy online today
www.specflue.com

SOLE DISTRIBUTOR
SPECFLUE