

FA3820 CO ALARM WITH 10 YEAR BATTERY


| | |
|---------------------|---------------------------------|
| Sensor type | ADVANCED ELECTROCHEMICAL |
| Battery type | SEALED FOR LIFE LITHIUM BATTERY |



- 10 year life featuring a 10 year sealed for life lithium battery
- Advanced electrochemical sensor calibrated and tested in CO gas
- Ventilate 'Pre alarm' warning: Low level monitoring function
- Quiet test function supports discreet testing at a lower volume when compared to standard CO alarms
- Intelligent algorithm heightens the sensitivity when detection of low level CO occurs - providing a rapid alert to dangerous CO levels
- Memory function – indication of previous alarm activation
- Advanced diagnostics support via cable
- Prominent visual alarm notification

Please note markings may vary depending on Country

Technical Specification



| | | |
|--------------------------------|---|--|
| Dimensions | 125mm (width) x 67mm (height) x 33mm (depth) | |
| Supply voltage | 3V DC | |
| Battery | 10 year sealed for life lithium battery | |
| Sensor Technology | Advanced Electrochemical | |
| Alarm sound level | 85dB(A) at 3m (minimum) | |
| Installation positions | Wall / Free-standing (<i>Portable - suitable for home and/or travel use</i>) | |
| For use in | Domestic premises including static and mobile homes, caravans, motor caravans and boats.* | |
| Operating temperature | -10 °C to +40 °C | |
| Operating humidity | 30 - 90% RH | |
| Storage temperature | -20 °C to +50 °C | |
| Storage humidity | 30-90% RH (non condensing) | |
| Plastic material | Fire Retardant ABS | |
| Warranty | 5 years | |
| Certified to | BS EN 50291-1:2018, BS EN 50291-2:2019 | |
| Independently tested by | BSI (certificate number KM 551504) | |
| Weight | 95g | |

